

3 AA BATTERIES

XPP-5418GX/RX-K01

INTRINSICALLY SAFE FLASHLIGHT

NIGHTSTICK[®]
Life Depends on Light™



Large, textured button that is **easy-to-use with gloves**



Durable polymer body is **impact & chemical resistant**



Non-conductive body for hazardous environments



Sharp focused flashlight beam for **distance illumination**

AVAILABLE IN MULTIPLE COLORS

XPP-5418RX-K01



200 LUMENS



1-800-233-2155 • 1-469-326-9400 • nightstick.com

© 2020 Bayco Products Inc. Items shown are intended as a visual representation for informational purposes only and are subject to change without notice. Visit nightstick.com for product updates.

INTRINSICALLY SAFE FLASHLIGHT

3 AA BATTERIES (not included)

ITEM NUMBER/UPC

- XPP-5418GX-K01, UPC 0 17398 80620 6
- XPP-5418RX-K01, UPC 0 17398 80622 0

MARKET APPLICATIONS

- Hazardous work environments, industrial, automotive, fire and rescue

CERTIFICATIONS

- cETLus, ATEX, IECEX, CE, NFPA, InMetro

CASE MATERIAL

- Engineered polymer

FLASHLIGHT LUMENS/RUNTIME

- 200L, 10.5 hrs. runtime

CANDELA

- 5,129

BEAM DISTANCE

- 143 m

WATER RATING

- ANSI IP-67 dustproof / waterproof

DROP RATING

- 2 meters

DIMENSIONS

- LENGTH: 5.6 in (142 mm)
- HANDLE DIAMETER: 0.75 in x 1.4 in (19 mm x 35 mm)
- HEAD DIAMETER: 1.5 in (38 mm)
- WEIGHT: 5.4 oz (153 g)

POWER SOURCE

- AA batteries (not included)

WARRANTY

- Limited lifetime

WHAT'S INCLUDED

- Flashlight
- Multi-angle mount

FL 1 STANDARD		
		
		


Bayco Products, Inc. XPP-5418GX/RX
 640 S. Sanden Blvd., Wylie, TX 75098

Ex ia FLASHLIGHT FOR USE IN HAZARDOUS LOCATIONS
 CLASS I DIV 1 GRPS A-D T3
 CLASS II & III DIV 1 GRPS E-G T135°C
 CLASS I ZONE 0 AEx ia IIC T3 Ga
 Ex ia IIC T3 Ga
 Ⓜ II 1 G Ex ia op is IIC T3 Ga

Ex ia op is IIC T3 Ga
 Intertek ITS 13 ATEX27837X
 IECEx ITS 16 0067X
 -20°C ≤ Tamb ≤ +40°C
 1.5V/Cell with three in series
 Energizer E91 or EN91

WARNINGS:
 Replace batteries in a non-hazardous location.
 Use only Energizer AA Model E91 or EN91 batteries.

AVERTISSEMENT:
 Remplacer les piles dans une zone non dangereuse.
 Utiliser uniquement les piles Energizer AA - modèle E91 ou EN91.

Segurança

 INMETRO OCP 0034
 03 09 06 10 10
 0375 0 2008 0 0070
 NCC 15.0288 X

CERTIFIED





