

3 AA BATTERIES

XPP-5458G

INTRINSICALLY SAFE DUAL-LIGHT HEADLAMP

NIGHTSTICK[®]
Life Depends on Light[™]



Includes a heavy-duty rubber, and a nylon head strap **for use on a hard hat.**



ANSI IP-67 Dustproof / Waterproof with a 2 meter drop rating.



Adjustable ratchet tilt head made from an engineered polymer housing



Balanced weight distribution, reduces neck fatigue.

CERTIFIED



190 LUMENS

1-800-233-2155 · 1-469-326-9400 · nightstick.com

© 2021 Bayco Products Inc. Items shown are intended as a visual representation for informational purposes only and are subject to change without notice. Visit nightstick.com for product updates.

INTRINSICALLY SAFE DUAL-LIGHT HEADLAMP

3 AA BATTERIES

ITEM NUMBER/UPC

- XPP-5458G, UPC 0 17398 80158 4

MARKET APPLICATIONS

- Hazardous work environments, industrial, automotive, law enforcement, fire & rescue

CERTIFICATIONS

- cETLus, CE, ATEX, IECEx, MSHA

CASE MATERIAL

- Engineered polymer

SPOTLIGHT LUMENS/RUNTIME

- WHITE: 130L, 14 hrs. runtime

FLOODLIGHT LUMENS/RUNTIME

- HIGH WHITE: 100L, 12 hrs. runtime
 - LOW WHITE: 25L, 70 hrs. runtime
 - GREEN: 21L, 37 hrs. runtime

DUAL-LIGHT LUMENS/RUNTIME

- 190L, 6 hrs. runtime

CANDELA

- 3,500

BEAM DISTANCE

- 120m

DUST/WATER RATING

- ANSI IP-67 dustproof / waterproof

DROP RATING

- 2 meters

DIMENSIONS

- LENGTH: 3.3 in (843 mm)
 - WIDTH: 3.3 in (84 mm)
 - DEPTH: 3.5 in (89 mm)
 - WEIGHT: 9.5 oz (269 g)

BATTERY







- AA

WARRANTY

- Limited lifetime warranty

WHAT'S INCLUDED

- Headlamp
 - Elastic non-slip headband
 - Rubber hardhat strap
 - 3 AA batteries

FL 1 STANDARD	SPOT HIGH	FLOOD LOW	DUAL-LIGHT
	130 LUMENS	21 LUMENS	190 LUMENS
	14h	37h	6h
	120m		
	3500cd		
	2m		
	1m		

Permissible Nightstick XPP-5458G Headlamp

MSHA APPROVAL No. 20-A130002-0

TESTED FOR INTRINSIC SAFETY IN METHANE-AIR MIXTURES ONLY

- WARNINGS:
- 1) MSHA approved for use with three AA Duracell Type PC1500, Energizer Type EN91, and Energizer Type L91 batteries only.
 - 2) Energizer Lithium (Type L91) batteries are to be replaced by a qualified technician only.
 - 3) Replace the batteries in fresh air only.
 - 4) Replace all batteries at the same time.
 - 5) Do not mix batteries from different manufacturers or of different types.
 - 6) The Model XPP-5458G Safety Headlamp must not be opened in areas where permissibility is required.
 - 7) The Model XPP-5458G Safety Headlamp is approved as a mine light under 30CFR, Part 20. It is not approve as a cap lamp under 30CFR, Part 19.



ID 4003544
 INTRINSICALLY SAFE
 SECURITE INTRINSEQUE

CE 2575

CLASS I DIV 1 GRPS A-D T3 Ex ia I Ma
 CLASS II & III DIV 1 GRPS E-G T135C Ex ia IIC T3 Ga
 CLASS I ZONE 0 Ex ia IIC T3 Ga Intertek ITS 13 ATEX27838X
 CLASS I ZONE 0 Ex ia IIC T3 Ga IECEx ETL 13.0025X
 © I M 1 Ex ia I Ma -20°C ≤ Tamb ≤ +40°C
 SECURITE INTRINSEQUE © II 1 G Ex ia IIC T3 Ga 1.5V/Cell AA Alkaline

Conforms to:

ANSI/UL STD 913, ANSI/UL 60079-0, ANSI/UL 60079-11
 ANSI/ISA 60079-26

Certified to:

CAN/CSA STD C22.2 No 157
 CAN/CSA STD C22.2 No 60079-0
 CAN/CSA STD C22.2 No 60079-11
 CSA STD C22.2 No 25

CERTIFIED

