

X-Series Intrinsically Safe Low-Profile Dual-Light™ Headlamp with Hard Hat Clip

Spot High Spot Low



Flood High Flood Low Dual



200 Lumens
Dual-Light™
180/100 Lumens
Spotlight
180/100 Lumens
Floodlight



TECHNOLOGY



- Low-profile design
- cULus, ATEX, and IECEx listed Intrinsically Safe
- Beam distance rated at 106 meters
- Polymer housing


This X-Series Intrinsically Safe Low-Profile Dual-Light™ Headlamp with Hard Hat Clip is cULus, ATEX and IECEx listed Intrinsically Safe. This headlamp features a multi-position tilt head design and includes an integrated Stainless Clip for attachment to most hard hat mounting brackets. Both the spotlight and the floodlight use LEDs and an advanced (TIR) Total Internal Reflection lens designed to optimize lumen output and beam pattern. Front mounted dual switches provide easy access to the spotlight for distance illumination, the floodlight for close-up illumination, and Dual-Light for maximum lighting, versatility and user safety. The XPP-5460GCX includes a hard hat mount for use on a fire helmet or hard-hat, and is powered by 3 AAA batteries (included).

INTRINSICALLY SAFE



XPP 5460GCX

X-Series Intrinsically Safe Low-Profile Dual-Light™ Headlamp



FEATURES

- cULus, ATEX and IECEx listed Intrinsically Safe
- LED technology
- Focused high/low-brightness spotlight beam for distance illumination
- Unfocused high/low-brightness wide-beam floodlight for close-up illumination
- Dual-Light™ (spotlight and floodlight on at the same time) for maximum versatility
- Glass-filled nylon polymer housing
- (TIR) Total Internal Reflection lens designed to optimize lumen output and beam pattern
- Dual switches located on front of light
- Adjustable tilt head
- Hard hat mount for fire helmets and hard hat applications
- Dustproof/Waterproof
- Impact & chemical resistant
- Powered by 3 AAA batteries (included)
- Limited Lifetime Warranty*

INCLUDED

- Headlamp
- 3 AAA batteries
- Hard hat mount

Model	UPC 0 17398
XPP-5460GCX	80605 3

SPECIFICATIONS

- Lumens: high spotlight-180, low spotlight-100, high floodlight-180, low floodlight-100, dual-light-200
- Run-time: high spotlight-3.5 hrs, low spotlight-10 hrs, high floodlight-3.5 hrs, low floodlight-10 hrs, dual-light-3 hrs
- Beam distance: 106 meters
- Water / Dust rating: IP-67
- Drop rating: 2 meters
- Length: 3.54in, width: 1.58in, depth: 1.875in, weight: 5.8oz

FL 1 STANDARD	DUAL-LIGHT	HIGH	LOW
	200 LUMENS	180 LUMENS	100 LUMENS
	3h	3h 30 min	10h
	78m	106m	74m
	1528cd	2799cd	1399cd
	2m		
	1m		

SAFETY RATING

cULus, ATEX, and IECEx listed Intrinsically Safe
Meets the requirements of NFPA-1971-8.6 (2013)

Bayco Products, Inc. XPP-5460
Wylie, TX 75098

cULus LISTED Ex ia FLASHLIGHT FOR USE IN HAZARDOUS LOCATIONS
E 467756 CLASS I DIV 1 GRPS A-D T4 Ex ia IIC T4 Ga
INTRINSICALLY SAFE CLASS II & III DIV 1 GRPS E-G DEMKO 17 ATEX 1824
SECURITE INTRINSEQUE CLASS I ZONE 0 GRP IIC T4 IECEX UL 17.0003
CE 0359 CLASS II ZONE 20 IIC T135°C -20°C ≤ Tamb ≤ +40°C
Ⓜ II 1 G Ex ia IIC T4 Ga 1.5V/Cell / E92 or EN92

WARNINGS:
Replace batteries in a non-hazardous location.
Use only Energizer Model E92 or EN92 batteries.

AVERTISSEMENT:
Remplacer les piles dans une zone non dangereuse.
Utiliser uniquement les piles Energizer AAA - modèle E92 ou EN92.

*Limited Lifetime Warranty • Product is warranted to be free from defects in workmanship and materials for the original purchaser's lifetime. The Limited Lifetime Warranty includes the LEDs, housing and lenses. Rechargeable batteries, chargers, switches, electronics and included accessories are warranted for a period of two (2) years with proof of purchase. Disposable, non-rechargeable batteries are excluded from this warranty. Normal wear and failures which are caused by accidents, misuse, abuse, faulty installation and lightning damage are also excluded.