

The Stinger HPL is a long-range, hand-held flashlight that produces a wide, 800 lumen beam pattern with brighter peripheral illumination and superior down-range performance.



<p>Four operating modes:</p> <ul style="list-style-type: none"> - High for a high lumen, far-reaching beam: 800 lumens; 438m beam distance; 48,000 candela; runs 1.5 hours - Medium for bright light and longer run time: 400 lumens; 310m beam distance; 24,000 candela; runs 2.5 hours - Low provides a less intense beam and extended run time: 200 lumens; 219m beam distance; 12,000 candela; runs 5 hours - Strobe for disorienting or signaling: runs 3 hours
<p>Optimized electronics provide regulated intensity</p>

<p>IPX4 water resistant 3 meter impact resistance tested</p>
<p>Serialized for positive identification</p>
<p>Stinger HPL: 9.23 in. (23.44 cm); 13.6 oz (385 grams) Stinger DS HPL: 9.65 in. (24.51 cm); 14.0 oz (396 grams)</p>
<p>Limited Lifetime Warranty Visit www.streamlight.com for full warranty information</p>
<p>See reverse for system configurations</p>

Item #	Item Description
Stinger HPL	
75982	Stinger HPL - IEC Type C (230V) AC/12V DC (NiMH)
75779	Stinger HPL - IEC Type G (240V) AC/12V DC (NiMH)
75763	Stinger HPL - IEC Type A (120V) AC/12V DC Smart Charge (NiMH)
75758	Stinger HPL - IEC Type A (100V) AC/12V DC (NiMH)
75981	Stinger HPL - IEC Type C (230V) AC(NiMH)
75778	Stinger HPL - IEC Type G (240V) AC (NiMH)
75761	Stinger HPL - IEC Type A (120V) AC Smart Charge (NiMH)
75757	Stinger HPL - IEC Type A (100V) AC (NiMH)
75799	Stinger HPL - 12V DC (NiMH)
75782	Stinger HPL - IEC Type A (120V) AC/12V DC PiggyBack Smart Charge (NiMH)
75980	Stinger HPL (WITHOUT CHARGER) (NiMH)
Stinger DS HPL	
75918	Stinger DS HPL - IEC Type C (230V) AC/12V DC SC (NiMH)
75879	Stinger DS HPL - IEC Type G (240V) AC/12V DC SC (NiMH)
75863	Stinger DS HPL - IEC Type A (120V) AC/12V DC Smart Charge (NiMH)
75858	Stinger DS HPL - IEC Type A (100V) AC/12V DC (NiMH)
75916	Stinger DS HPL - IEC Type C (230V) AC(NiMH)
75878	Stinger DS HPL - IEC Type G (240V) AC (NiMH)
75861	Stinger DS HPL - IEC Type A (120V) AC Smart Charge (NiMH)
75857	Stinger DS HPL - IEC Type A (100V) AC (NiMH)
75899	Stinger DS HPL - 12V DC Smart Charge (NiMH)
75882	Stinger DS HPL - 120V AC/12V DC Smart Charge PiggyBack (NiMH)
75900	Stinger DS HPL - (WITHOUT CHARGER) (NiMH)

