



## PRODUCT FACT SHEET

### TLR-6® TACTICAL LIGHT WITH RED LASER DESIGNED FOR USE WITH TAURUS GX4™

- DESCRIPTION:** The ultra-compact TLR-6® weapon light with high power LED and integrated red aiming laser features tool-less battery replacement without removal from the weapon or the need to re-sight the laser. The light provides 1 hour of regulated run time when in dual light/laser mode. Designed to securely attach to the rail and trigger guard of the Taurus GX4™ micro-compact handgun.
- CASE MATERIAL:** Impact-resistant engineered polymer. Available in black.
- DIMENSIONS:** Length: 2.5 in. (6.35 cm)      Width: 0.85 in. (2.16 cm)      Height: 1.56 in. (3.96 cm)
- WEIGHT:** 1.12 oz. (32 grams) with batteries (included with purchase).
- LENS:** Glass with shock-resistant gasket seal.
- LIGHT SOURCE:** LED, white, impervious to shock with a 50,000-hour lifetime.  
640-660nm red laser.
- LIGHT OUTPUT:** 100 lumens, 2,000 candela peak beam intensity and an 89-meter beam distance. Parabolic reflector produces a balance of beam and peripheral illumination. Optimized electronics provide regulated intensity. Laser provides long-range targeting.
- ON/OFF:** Left- and right-hand switches for ambidextrous operation. Quick press of either switch for constant on operation or press and hold for momentary operation.  
3 modes: Laser only, dual mode or light only; selectable by quick press of both switches.
- RUN TIME:** LED only or LED/Laser: 1-hour total regulated run time to the 10% output level.  
Laser only: 11 hours total regulated output.  
All modes feature a 10-minute auto shut-off to maximize battery life.
- BATTERY:** Two (2) 3-Volt CR-1/3N lithium coin batteries (IEC CR11108) with a storage life of 10 years. Batteries replaceable with unit mounted on weapon. No need to re-sight laser after each battery change.
- FEATURES:** Designed for use with Taurus GX4™ micro-compact handguns.  
Ultra lightweight and compact.  
Ambidextrous operation.  
Windage and elevation adjustment screws mounted in bushings for long life and dependable zero retention of laser.  
Operating temperature: -20° F to +120° F.  
1-meter impact resistance tested.  
Serialized for positive identification.
- APPROVALS:** N/A
- WARRANTY:** Streamlight's Limited Lifetime Warranty.
- OPTIONAL ACCESSORIES:** N/A

All Rights Reserved. Taurus™ and GX4™ are trademarks of Taurus International Manufacturing, Inc. Streamlight has not sought endorsement of this product from Taurus International Manufacturing, Inc.

**EXPORT CONTROLS:** The export of this product is subject to the jurisdiction of the U.S. Department of Commerce Export Administrative Regulations ("EAR"). The exported sale, transfer or shipment of this product is expressly prohibited by U.S. Law and is subject to export restrictions, including export licenses and accompanying documentation and authorization, the absence of which may result in fines and penalties. Furthermore, diversion, resale, re-export or transfer of this product is contrary to U.S. Law and is prohibited without the prior written consent of the U.S. Department of Commerce. Compliance with any and all export controls are the sole responsibility of the distributor.

Issued: 12/20/2021

Revised:

Rev: 0

Assembled in the USA.

Document # 380